

### **Amendments to the Claims**

The following listing of the claims will replace all prior versions, and listings of the claims in the application:

### **Listing of Claims**

1. (Currently amended) An image communication apparatus for use in an image communication network system including a computer network being able to transmit and receive an image, based on a network address, a first telephone network being able to transmit and receive said image based on a first telephone number, a second telephone network being able to transmit and receive said image based on a second telephone number, a first address supplying device connected to said computer network adapted to store correspondence between said first telephone number and said network address corresponding to said first telephone number, and a second address supplying device connected to said computer network adapted to store correspondence between said second telephone number and said network address corresponding to said second telephone number, comprising:

an input section to input either of said first telephone number or said second telephone number provided to another image communication apparatus to which said image is to be transmitted, the first telephone number corresponding to said first telephone network and the second telephone number corresponding to said second telephone network;

a judging section to judge whether said telephone number input through said input section ~~is able to be used~~ corresponds to said first telephone network or said second telephone network;

a number transmitting section to transmit said input telephone number, based on a ~~judgement~~ judgment result by said judging section, to ~~either of~~ said first address supplying device if the input telephone number corresponds to said first telephone network, or to said second address supplying device if the input telephone corresponds to said second telephone network,

an address receiving section to receive, in response to said telephone number fed from said telephone number transmitting section, a network address corresponding to said input telephone number; and

an image transmitting section to transmit, based on said network address received by said address receiving section, said image to said another image communication apparatus through said computer network.

2. (Original) The image communication apparatus according to Claim 1, wherein said judging section judges whether said input telephone number has been registered.

3. Canceled

4. (Original) The image communication system according to Claim 1, wherein said image communication apparatus is provided with said first address supplying device and said second address supplying as function sections of said image communication apparatus.

5. (Original) The image communication device according to Claim 1, further comprising a second image transmitting section to transmit images to said another image communication apparatus through either of said telephone network for use in said first telephone number or said telephone network for use in second telephone number.

6. (Original) The image communication device according to Claim 5, further comprising a signal receiving section to receive, when said second image transmitting section transmits a first image, using either of said first telephone number or said second telephone number, to said another image communication apparatus through either of said telephone network for use in said first telephone number or said telephone network for use in second telephone number, a signal containing a computer address provided to said image communication apparatus on a receiver side which is returned, in response to said transmitting of said image, from said another image communication apparatus and wherein said first image transmitting section is adapted to transmit a second image contained in said signal received by said signal receiving section, based on said computer address of said another image communication apparatus, to said another image communication apparatus through said computer network.

7. (Original) The image communication apparatus according to Claim 6, further comprising a storage section to store correspondence between said telephone number used by said image transmitting section when said first image is transmitted and received through either of said telephone network for use in said first telephone number or said telephone network

for use in said second telephone number and said network address of said another image communication apparatus received by said signal receiving section when said first image is received.

8. (Original) The image communication apparatus according to Claim 5, wherein said second image transmitting section, when said first image transmitting section fails to transmit said image based on said computer address through said computer network, transmits said image using either of said first telephone number or said second telephone number through either of said telephone network for use in said first telephone number or said telephone network for use in said second telephone number.

9. (Original) The image communication apparatus according to Claim 5, further comprising an operation section to designate to which priority is given, transmission by said first image transmitting section through said computer network or transmission by said second image transmitting section through said telephone network.

10. (Original) The image communication apparatus according to Claim 9, wherein said operation section, when said first image transmitting section fails to transmit said image through said computer network, designates whether said image is to be transmitted by said second image transmitting section through said telephone network.

11. (Original) The image communication apparatus according to Claim 1, wherein said first telephone network is an inside telephone network that is able to transmit and receive said image based on said first telephone number being said inside telephone number and said second telephone network is an outside telephone network that is able to transmit and receive said image based on said second telephone number being said outside telephone number and wherein said computer network is either of an intranet or the Internet that is able to transmit and receive said image based on said network address being an IP (Internet Protocol) address.

12. (Original) The image communication apparatus according to Claim 1, wherein said number transmitting section transmits said input number through said computer network and said address receiving section receives said network address through said computer network.

13. (Currently amended) An image communication system comprising:  
a computer network being able to transmit and receive an image based on

a network address;

a first telephone network being able to transmit and receive said image based on a first telephone number corresponding to said first telephone network;

a second telephone network being able to transmit and receive said image based on a second telephone number corresponding to said second telephone network;

a first address supplying device connected to said computer network adapted to store correspondence between said first telephone number and said network address corresponding to said first telephone number;

a second address supplying device connected to said computer network adapted to store correspondence between said second telephone number and said network address corresponding to said second telephone number; and

a plurality of image communication apparatuses to send and receive said image mutually through any one of said computer network, said first telephone network and said second telephone network; ~~and~~

wherein each of a plurality of said image communication apparatuses includes an input section to input either of said first telephone number or said second telephone number provided to another image communication apparatus to which said image is to be transmitted, a judging section to judge whether said telephone number input through said input section ~~is able to be used~~ corresponds to said first telephone network or said second telephone network, a number transmitting section to transmit said input telephone number, based on a ~~judgement~~ judgment result by said judging section, to ~~either of~~ said first address supplying device or to said second address supplying device, an address receiving section to receive, in response to said input telephone number fed from said telephone number transmitting section, a network address corresponding to said telephone number; and an image transmitting section to transmit, based on said network address received by said address receiving section, said image to said another image communication apparatus through said computer network.

14. (Original) The image communication system according to Claim 13, wherein said judging section judges whether said input number has been registered.

15. Canceled

16. (Original) The image communication system according to Claim 13,

wherein said image communication system is provided with, as its function section, either of said first address supplying device or said second address supplying device.

17. (Original) The image communication system according to Claim 16, wherein said image communication apparatus further includes an operation section to designate either of said image communication apparatus having either of said first address supplying device or said second address supplying device as a device from which said network address is acquired.

18. (Original) The image communication system according to Claim 13, wherein said number transmitting section transmits said input number through said computer network and wherein said address receiving section receives said network address through said computer network.

19. (Currently amended) An image communication method ~~comprising~~ for carrying out image communication with another image communication apparatus, based on a computer address, through a computer network, comprising:

receiving a telephone number of said another image communication apparatus;

judging whether said received telephone number corresponds to a first telephone network or a second telephone network ~~is a first telephone number or a second telephone number, where the first telephone number;~~

acquiring a computer address corresponding to said ~~first~~ telephone number, when said telephone number is judged to ~~be said first telephone number~~ correspond to the first telephone network by referring to a first table showing correspondence between said ~~first~~ telephone number and said computer address;

acquiring a computer address corresponding to said ~~second~~ telephone number, when said telephone number is judged to correspond to the second telephone network ~~be said second telephone number~~, by referring to a second table showing correspondence between said ~~second~~ telephone number and said computer address; and

transmitting said image to said another communication apparatus based on said acquired computer address.

20. (Original) The image communication method according to Claim 19,

further comprising:

second transmitting said image to said another image communication apparatus, based on said first telephone number, through a first telephone network and a second telephone network; and

selectively performing either of said first transmitting and said second transmitting.

21. (Original) The image communication method according to Claim 19, wherein, in said selectively performing either of said first transmitting and said second transmitting, priority is given to said first transmitting rather than to said second transmitting.

22. (Original) The image communication method according to Claim 19, wherein, in selectively performing either of said first transmitting and said second transmitting, when a failure occurs in said first transmitting, said second transmitting is performed.

23. (Original) The image communication method according to Claim 19, further comprising:

receiving a signal which is to be received from said another image communication apparatus through either of said first telephone network or said second telephone network and which contains a computer address of said another image communication apparatus;

extracting a computer address of said another image communication apparatus from said received signal; and

wherein said first transmitting is used to transmit said image, based on said extracted computer address, through said computer network to said another image communication apparatus.

24. (New) An image communication system comprising:  
a first image communication apparatus for transmitting an image in either  
outside communication or inside communication;  
a second image communication apparatus for receiving an image in either  
outside communication or inside communication;  
a first address supplying device used in outside communication; and  
a second address supplying device used in inside communication, said first  
communication apparatus, said second communication apparatus, said first address supplying

device and said second address supplying device being connected together via a computer network, wherein said first image communication apparatus includes an input section to input either an outside telephone number or an inside telephone number, said outside telephone number corresponding to outside communication and the inside telephone number corresponding to inside communication, a judging section to judge whether said telephone number input through said input section is the outside telephone number or the inside telephone number, a number transmitting section to transmit said input telephone number, based on a judgment result by said judging section, to said first address supplying device or to said second address supplying device, an address receiving section to receive, in response to said input telephone number fed from said telephone number transmitting section, a network address corresponding to said telephone number; and an image transmitting section to transmit, based on said network address received by said address receiving section, said image from said first communication apparatus to said second communication apparatus through said computer network.

25. (New) The image communication system according to claim 24, wherein the first image communication apparatus and the second image communication apparatus each respond to an outside telephone number used for outside communication, an inside telephone number used for inside communication, and a network address.

26. (New) The image communication system according to claim 24, wherein the first address supplying device stores a corresponding relation between the outside telephone number and the IP address.

27. (New) The image communication system according to claim 24, wherein the second address supplying device stores a corresponding relation between the inside telephone number and the IP address.

28. (New) The image communication system according to claim 24, further including a communication control section which, when a telephone number is inputted, judges the whether the telephone number is the outside telephone number or the inside telephone number of the second image communication apparatus; and if it is the outside telephone number, connects

to the first address supplying device to obtain the IP address based on the outside telephone number; and if it is the inside telephone number, connects to the second address supplying device to obtain the IP address based on the inside telephone number; then on the basis of the obtained IP address, transmits an image to the second image communication apparatus.